



## Specifications

### WALLS

16mm (12mm finished) T&G Shiplap cladding on all models fixed to an internal framework consisting of sturdy 47mm x 47mm (45mm x 45mm finished) vertical framework on Shoreham and Tangmere models and 47mm x 20mm (45mm x 18mm finished) framework on the Donnington Apex and Pent models. There is an option to upgrade the Shoreham buildings to 19mm (15mm finished) T&G Shiplap or Loglap if desired for a small extra cost.

### FLOOR

16mm (12mm finished) T&G matchboard floor on 47mm x 47mm pressure treated floor joists with an option to upgrade to a heavy duty 18mm Caberboard floor.

### ROOF

16mm (12mm finished) T&G on sturdy roof purlins and covered with a heavy duty polyester based roofing felt.

### BUILDING STYLES

**Donnington Apex** - This building features a 0.76m (2' 6") wide door (left or right hinged to suit) which is fitted with a brenton padbolt and hung within the narrow gable end. One side elevation will feature fixed window(s) and the internal height is 1.73m (5' 8") at the eaves raising to 1.96m (6' 5") at the ridge.

**Donnington Pent** - Features a 0.76m (2' 6") wide door (left or right hinged to suit) which is fitted with a brenton padbolt and hung to one corner of the high elevation. There will be fixed windows to the side of the door (also on the high elevation) and the internal height is 1.73m (5' 8") at the rear raising to 1.96m (6' 5") at the front.

**Shoreham Narrow Shed** - Do you have an unused gap to the side of the house or behind your log cabin? This unique building will enable you to reclaim that otherwise wasted space and put it to good use. The building has a 0.6m (2') wide door (fitted with a rimlock and handle) offset to the highest side of the 0.9m (3') wide pent end and boasts internal height of 1.73m (5' 8") on the low wall raising to 1.96m (6' 5") at the high point. The building can go in any location however if going in to a restricted space then there must be an absolute minimum of 1.01m (3' 4") at roof height to accommodate the roof overhang and we would recommend the upgrade to the 19mm (15mm finished size) T&G Shiplap cladding with Premier Treatment to extend the life of the building.

**Tangmere Storage Box** - A handy storage box with an internal height of 1.12m (3' 8") at the front raising to 1.24m (4' 1") at the rear. There is a single 0.76m (2' 6") wide door (fitted with brenton padbolt) hung to the centre of the low wall which will be 1.2m (4'), 1.5m (5') or 1.8m (6') wide. The depth of the building is 0.76m (2' 6") in all instances.

- Simple solid designs
- Hand made to order
- Optional lining and insulation
- Free on-site installation
- Choice of four window styles

All specifications are subject to change.  
All sizes are nominal. E&OE.



1.8m x 1.2m (6' x 4') Donnington Apex and 2.1m x 1.5m (7' x 5') Donnington Pent Sheds on display at our Sutton Green display site

## Diamond Storage Sheds

A selection of four simple - yet well constructed - storage buildings that will make a useful addition to any garden. Whilst these buildings represent exceptional value for money; standards remain as high as on all other buildings from within our Diamond range.



1.2m x 0.76m (4' x 2' 6") Tangmere Storage Box



2.4m x 1.8m (8' x 6") Donnington Pent shed



1.8m x 1.2m (6' x 4') Donnington Apex shed



1.5m x 0.9m (5' x 3') Shoreham Narrow Shed



2.4m x 0.9m (8' x 3') Shoreham Narrow Shed